



# Ox-Off POOL CLEANER

**LIME, SCALE AND SCUM REMOVER**  
RUST • LIME • SCALE • MINERAL DEPOSITS

## DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.

May cause respiratory irritation.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:**  1  5  20  35  55 Gallon(s)

# Ox-Off POOL CLEANER



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

**IF SWALLOWED:** rinse mouth. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Call a doctor, a POISON CENTER if you feel unwell.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

## **WARNING:**

This product can expose you to 1,4-dioxane which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



Removes scum and slime, lime, minerals and scale from hard surfaces such as metal or tile swimming pools, shower walls and floors. Prepares pool surfaces for painting.

## **DIRECTIONS**

Dilute 1 part of **OX-OFF POOL CLEANER** with 3 to 5 parts water, depending upon amount of scale and speed required to perform the job. Apply this solution with sponge or mop to walls and floor. Allow to act for about 5 minutes then rinse thoroughly with water. Stubborn deposits may require a second treatment. For use in high pressure washers, Dilute **OX-OFF POOL CLEANER** with 3 to 5 parts water.

## **NFPA® Ratings**

Health: 1; Flammability: 0; Reactivity: 0

## **Contains/CAS Number:**

Water (7732-18-5); Hydrochloric Acid (7647-01-0); Linear Alcohol Ethoxylate (34398-01-1); Tallow Alkyldiamine Ethoxylate (61790-85-0); Surfactant (Proprietary).

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0140.041520