

SEWAGE BUILD-UP REMOVER

LOOSENS AND DISSOLVES GREASE & FATS

DANGER

Flammable liquid and vapor. Harmful in contact with skin or if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 1 5 20 35 55 Gallon(s)





P.O. Box 245013 Milwaukee, WI 53224 (800) 776-7192 www.sharecorp.com

DANGER dentry iness. May cause genetic defects. May cause ig fertility or the unborn child. Causes damage prolonged or repeated aposure

Do not handle until all safety precaution open flames, sparks, No smoking. Keep container tightly closed receiving equipment. Use explosion-proof electrical. lighting, ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe fume, mist, spray, vapors, Avoid breathing mist, spray, vapors, Wash thoroughly after handling, Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.Wear protective clothing, protective gloves, eye protection face protection. Take off contaminated clothing and wash it before reuse.

RESPONSE:

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing If exposed or concerned: Get medical advice/attention, Call a doctor, a POISON CENTER if you feel unwell. Take off contaminated clothing and wash it before reuse In case of fire: Use alcohol resistant foam, Water spray, dry extinguishing powder, carbon dioxide (CO2) to extinguish.

STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

DISPOSAL:

Dispose of contents/container to comply with local/regional/national/ international regulations.





FLOATING LIFT STATION DEGREASER is an emulsifiable solvent degreaser designed to dissolve grease and fats in lift stations, sewer lines, and grease traps. Because it is lighter than water, it will float on the surface of the water to strip grease and fats from the sides of lift stations as the water level rises and falls. Special emulsifiers allow the solvent and dissolved grease to be dispersed into the water for complete removal.

DIRECTIONS:

Use 1/2 gallon of FLOATING LIFT STATION DEGREASER per square foot of water surface. Apply when lift station is at lowest level by spraving or pouring down the wall of the lift station.

NOTE: Because FLOATING LIFT STATION DEGREASER is an emulsifiable solvent, care must be take to prevent immediate mixing of the solvent and water. Direct pouring or splashing into the water will cause the degreaser to be dispersed before it can remove the grease, thus destroying its effectiveness

NFPA[®] RATINGS:

Health: 2: Flammability: 3: Reactivity: 0

INGREDIENT/CAS #:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8) Solvent naphtha (petroleum), light aliphatic (64742-89-8); Xylene (1330-20-7); Ethylbenzene (100-41-4).

For industrial and commercial use only

For additional information, see Safety Data Sheet.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.



0156.050715