CONGENTRATED, EASY TO USE FASTANG THE REMOVES DIRT, GREASE, FATS, OIL AND SAREON

CORP

DANGER

Toxic if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage.

KEEP OUT OF REACH OF CHILDREN NET CONTENTS: 1 5 20 35 55 Gallon(s)

PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com

CORP

_

mist, vapours Wash thoroughly after eat drink or smoke when using this product. Wear evel protection, protective gloves. ve clothing. Store locked bo.

IR SWALLOWED: Rinse mouth. Immediately call a doctor, POISON CENTER DO NOT induce vomiting JFON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing. Immediately call a POISON CENTER, doctor. Call a doctor. POISON CENTER if you feel unwell.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.







LIFT STATION AND SEWER LINE CLEANER is a fast acting odorless liquid specifically designed to eliminate grease problems in lift stations, sewer plants, septic tanks, grease traps, cesspools, and drainage fields. This special formula is heavier than water to sink below the water line to the point of obstruction and dissolve the congestive grease, oils, lint and other organic matter at the source.

DIRECTIONS

Pour 8 to 10 gallons of LIFT STATION AND SEWER LINE **CLEANER** into the sump or manholes as close as possible to the obstruction. For best results, use LIFT STATION AND SEWER LINE CLEANER regularly to keep lift station and sewer lines open and free flowing. For the removal of difficult obstructions, a second application may be necessary.

NFPA[®] RATINGS

Health: 3; Flammability: 0; Reactivity: 1

INGREDIENTS/CAS #:

Sodium Hydroxide/1310-73-2; Water/7732-18-5; Potassium Hydroxide/1310-58-3

0255.011615