



Silt & Sand REMOVER

SILT SUSPENDING AGENT

Removes mud, dirt and silt from sewers



KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □ 1 □ 5 □ 20 □ 35 □ 55 Gallon(s)



Silt & Sand REMOVER

SILT SUSPENDING AGENT



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

NFPA® RATINGS:

Health: 0; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Non-Ionic Water Soluble Polymer (Proprietary); DMDM Hydantoin (Mixture); 1,1'-Oxydipropan-2-ol (110-98-5); 1,2-Benzisothiazol-3(2H)-one (2634-33-5).

⚠️ WARNING:

This product can expose you to acrylamide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SILT & SAND REMOVER is designed to break up and disperse organic and inorganic deposits that may accumulate in sewers. When used with a program of regular cleaning and flushing, it helps keep piping, wells and basins free-flowing and clear of deposits.

DIRECTIONS:

Use at a rate of 1/2 to 1 gallon for each 1000 gallons of flushing water.

RECOMMENDED DOSAGES PER 400 FEET:

4" Line	2 to 4 gallons
6" Line	4 to 6 gallons
8" Line	6 to 8 gallons
10" Line	8 to 10 gallons

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



Please Recycle.

0380.020718