

SALT DEFENSE

Protective Salt Rust and Corrosion Barrier

Form: Liquid

Color: Clear, Colorless Liquid

Odor: Lemon-like

pH: No Data Available

Solubility (in water): No Data Available

(in mineral spirits): No Data Available

VOC Content: > 90%

Flash Point (ASTM D-7821): 103°F

Specific Gravity: 0.79 g/ml

Storage Stability (at 70°F): 1 year

Features

- **Applies Quickly**
- **Dries Smooth/Fast**
- **Ultra-Clear Finish**
- **Works Indoors and Outdoors**
- **Long-Lasting**

Ingredients

Distillates (Petroleum), Hydrotreated Light
 Polydimethylsiloxane
 Fragrance
 Toulene
 Benzene

C.A.S.

64742-47-8
 63148-62-9
 Mixture
 108-88-3
 71-43-2

DIRECTIONS: Apply with a sprayer, paint roller or brush. For best results and longer life, wash equipment thoroughly and allow to dry before applying **Salt Defense**. Two light coats, allowing one hour of drying time between applications, will provide good protection and prevent unwanted deposits from bonding to the surface. For maximum protection, apply **Salt Defence** at the end of each work period. Several applications over summer storage periods will preserve equipment.

CONSULT PRODUCT LABEL FOR DETAILED USE DIRECTIONS.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	2
Flammability	Moderate	2	Moderate	Flammability	2
Reactivity	Slight	1	Slight	Reactivity	0