

# BIO-FLOW BLOCKS

## Bacterial Grease Trap/Sewer Line Treatment



**Form:** Solid  
**Color:** Light Red  
**Odor:** None  
**pH:** N/A  
**Solubility (in water):** Complete  
**(in mineral spirits):** Insoluble  
**VOC Content (% by weight):** N/D  
**Flash Point (ASTM D-7821):** N/A  
**Specific Gravity:** N/D  
**Density:** N/D  
**Bacterial Count:** 4 billion CFU/gram  
**Storage Stability (at 70°F):** 1 year  
**Ingredients** **C.A.S. #**  
 Genus Bacillus .....No CAS Number

**Use it for...**

- **Waste Water Plants**
- **Holding Tanks**
- **Waste Pumps**
- **Oxidation Ditches**
- **Lift Stations**
- **Activated Sludge**
- **Lagoons**
- **Reactors & Contractors**

**To reduce...**

- **Odor**
- **Sludge**
- **Fats**
- **Oils**
- **Grease Buildup**

### DIRECTIONS FOR USE:

BIO-FLOW BLOCKS will dissolve gradually over a 30-90 day period (depending upon flow rate) allowing for continuous treatment of waste. Each block is packaged in a heavy nylon mesh bag allowing suspension of the block.

**Easy to use:** Remove block from box. Suspend block from a rope into area to be treated. Replace block when dissolved, approximately every 30 – 90 days.

### Degradation Flow Rates:

5 lb. block: 75 – 250 thousand gallons/day.  
 30 lb. block: ≥ 1 million gallons/day.

HMIS				NFPA	
		Severe	4	Extreme	
Health .....	0	Serious	3	High	Health .....
Flammability .....	0	Moderate	2	Moderate	Flammability .....
Reactivity .....	0	Slight	1	Slight	Reactivity .....
Personal Protection .....	None	Minimal	0	Insignificant	Special Precautions .....
					None