



FOAMING SEWER CLEANER & DEGREASER

CONCENTRATED FOAMING SEWER DEGREASER

DANGER

Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

FOAMING SEWER CLEANER & DEGREASER



**P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com**



DANGER:

Causes serious eye damage.

Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS:

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS#:

Water/7732-18-5; Linear Alcohol Ethoxylate/
34398-01-1; Ethoxylated Alkyl Amine/68478-95-5;
Amine Oxide/68478-65-9; Isopropanol/67-63-0



Please Recycle.

FOAMING SEWER CLEANER & DEGREASER is a grease liquefier specially designed to quickly eliminate grease from sewer lines with minimal effort. The foaming action of the **FOAMING SEWER CLEANER & DEGREASER** ensures most pipes will be left virtually free of grease after just one pass when combined with the high pressure of a jet truck. After the **FOAMING SEWER CLEANER & DEGREASER** has been added and the grease has liquefied, the liquid grease washes downstream and will not re-coagulate. In the future, prevent clogged lines and sewer backups using Share's **FOAMING SEWER CLEANER & DEGREASER**.

DIRECTIONS:

Not recommended for household use. In a high pressure jet truck dilute 1 gallon of **FOAMING SEWER CLEANER & DEGREASER** in 100 gallons of water to treat approximately 100 feet of sewer pipe. Jet spray the **FOAMING SEWER CLEANER & DEGREASER** upstream from the affected pipe. Allow **FOAMING SEWER CLEANER & DEGREASER** 10 - 15 minutes to liquefy grease before jet spraying and retrieval.

The jet sprayer pressure should be set to maximum PSI and reel speed. Turn the water pressure off after the jet sprayer hose has been stopped at the upstream manhole. Wait 10 minutes and the grease will be homogenized.

For best results, use a rotating jet sprayer nozzle. Treat any excess foaming with 1 quart **BUBBLE BUSTER** per 100 gallon tank mix.

FOAMING SEWER CLEANER & DEGREASER

0615.060615