



BoilerPro Fuel Plus

SPECIMEN LABEL

COMBUSTION CATALYST

CAUTION: COMBUSTIBLE

May irritate eyes. See back panel for further precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 □ 5 □ 20 □ 35 □ 55 □ Gallons



BoilerPro Fuel Plus



P.O. Box 245013
 Milwaukee, WI 53224
 (800) 776-7192
 www.sharecorp.com

TRIDENT BOILERPRO FUEL PLUS is an easy to handle liquid designed for use in fuel systems where problems exist both in the storage tank and at fireside. TRIDENT BOILERPRO FUEL PLUS reduces the viscosity of residual fuel oils and has a fluidizing effect at all temperatures, which provides more uniform and faster pumping. Sludge that typically clogs fuel stainers, nozzles, preheaters and lines is dispersed throughout the fuel. TRIDENT BOILERPRO FUEL PLUS makes the organic/inorganic deposits in the fuel system and at the burners more friable. It forms a protective film on internal surfaces of storage tanks and piping to reduce corrosion and deposit build-up. TRIDENT BOILERPRO FUEL PLUS combines an organic combustion catalyst, emulsifying agents and solvents to protect boiler tubes and refractory brickwork by deactivating the vanadium oxides and sodium salts. It provides superior protection against cold-end stack corrosion. Fuel oil treated with TRIDENT BOILERPRO FUEL PLUS burns cleaner and more completely thereby reducing emission problems associated with particulates, sulfur dioxide and sulfur trioxide.

DIRECTIONS

It is advisable to add TRIDENT BOILERPRO FUEL PLUS directly to the fuel oil storage tank just before the tank is refilled so that incoming oil will provide sufficient agitation and mixing.

Initial dose: 2 gallons per 1000 gallons of fuel oil (1 quart per 125 gallons).

Maintenance dose: 1 quart per 1000 gallons of fuel oil (4 ounces per 125 gallons).

CAUTION: COMBUSTIBLE

May irritate eyes. Avoid contact with eyes. Do not take internally.

FIRST AID

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove contaminated clothing and laundry before reuse. Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Give affected person several glasses of water.

Do not induce vomiting. Never give anything to an unconscious person.

IF INHALED: Remove person to fresh air. If irritation persists, obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

INGREDIENTS	CAS NUMBER
Light Aromatic Solvent Naphtha	.64742-95-6
1,2,4 - Trimethylbenzene	.95-63-6
Fuel Oil Conditioner	Proprietary
Corrosion Inhibitor	Proprietary
Xylene	.1330-20-7

NFPA RATINGS
 Flammability

