

HEAVY DUTY LIQUID DRAIN OPENER

Concentrated Acid Drain Opener

Form: Liquid

Color: Red to Amber

Odor: Odorless

pH: <1.0

Solubility (in water): Complete
(in mineral spirits): Insoluble

VOC Content (% by weight): N/D

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.84 ± 0.05 g/cm³

Density: 15.36 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Sulfuric Acid.....	7664-93-9
Water.....	7732-18-5

- | Other Uses... |
|------------------------------|
| • Neutralize Alkaline Spills |
| • Increase Soil Acidity |
| • Lift Station Degreaser |
| • Grease Trap Cleaner |

DIRECTIONS: FOR COMPLETELY CLOGGED DRAINS: Remove standing water before pouring. Pour 4 ounces of HEAVY DUTY LIQUID DRAIN OPENER into the drain. Using more than 4 ounces could generate excessive heat, causing toilet bowls to crack. Allow to stand 15 minutes. Carefully and slowly add 4 ounces of water. Wait 5 minutes then slowly run cold water. If drain is still clogged, repeat this process.

FOR PARTIALLY CLOGGED DRAINS: Pour 4 ounces of HEAVY DUTY LIQUID DRAIN OPENER into drain. Let stand for 5 minutes. Repeat this procedure then flush several times.

DANGER: CONCENTRATED SULFURIC ACID. FOR PROFESSIONAL OR QUALIFIED MAINTENANCE PERSONNEL ONLY. NOT FOR HOUSEHOLD USE OR RETAIL SALE.

HMIS				NFPA	
		Severe	4	Extreme	
Health.....	3	Serious	3	High	Health.....
Flammability.....	0	Moderate	2	Moderate	Flammability.....
Reactivity.....	2	Slight	1	Slight	Reactivity.....
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....
					None