



Silica SOIL BINDER

SOIL BINDING AGENT

BINDS SOIL PARTICLES TO PROMOTE SOIL COMPACTION AND CONTROL DUST.

DANGER

Causes skin irritation. Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)



Silica SOIL BINDER

SOIL BINDING AGENT



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**



DANGER: Causes skin irritation. Causes serious eye damage.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water/7732-18-5; Sodium Silicate/1344-09-8



Please Recycle.

SILICA SOIL BINDER cements soil particles together to compact and increase load bearing capacity of unpaved roadways. It eliminates powdering of fine soils and holds down dust while stabilizing roadways for longer life and fewer repairs. **SILICA SOIL BINDER** is non-toxic and tanks used for application may be used to transport potable water.

DIRECTIONS:

Coverage: 1.2 - 11.2 gallons per 10,000 sq. ft.

For Stabilizing Smooth Roads and For Dust Control: Dilute 6 gallons of **SILICA SOIL BINDER** in 1000 gallons of water and apply this solution at a rate of 20 gallons per 1000 square feet. Repeat this procedure for three consecutive days. Use of Share's **SURFACTANT** at a dilution of 1 gallon per 1000 gallons of water will increase penetration of the solution and help control dust. When dusting problem returns, repeat application.

For Stabilizing Worn Roads or New Roads: 1.) Rip road to sub-base or 6 inches if possible. 2.) Windrow loose soil. 3.) Wet road base with a solution of 6 gallons of **SILICA SOIL BINDER** in 1000 gallons of water (or less with high evaporation rate) and apply this solution at a rate of 20 gallons per 1000 square feet. 4.) Bring the road base back in 2-inch lifts, wetting to optimum moisture with the above solution. Pack each lift. 5.) When all lifts are back, shape and crown road. 6.) Wet road with a solution of 1 gallon **SILICA SOIL BINDER** in 1000 gallons of water to moisten road and pack top layer. 7.) Repeat step 6 for two consecutive days.

1292.052915