



# Liqui-Gem

# DIAMOND

**20% SOLIDS THERMOPLASTIC FLOOR FINISH**

**CROSSLINKED ACRYLIC FINISH**

**CONTAINS 20% NON-VOLATILE SOLIDS**

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)**

## Liqui-Gem DIAMOND



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



## Liqui-Gem

# DIAMOND

**DISPOSAL:** Offer empty container for recycling. If recycling is not available, discard container in trash.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**NFPA® RATINGS:**

Health: 0; Flammability: 1; Reactivity: 0

**INGREDIENTS/CAS #:**

Acrylic Polymer/Proprietary; Water/7732-18-5;  
Diethylene Glycol Monoethyl Ether/111-90-0;  
Tributoxyethyl Phosphate/78-51-3; Zinc  
Oxide/1314-13-2

**APPLICATION DIRECTIONS:**

- Remove old wax or finishes using **LIQUI-GEM MARQUISE CUT**.
- Neutralize stripper residue utilizing **LIQUI-GEM BALANCE**.
- Rinse floor with water and allow to dry.
- Seal floor surface with 2 coats of **LIQUI-GEM SETTING**.
- Apply 2 smooth, even coats of **LIQUI-GEM DIAMOND** using a previously rinsed cotton string mop or lamb's wool applicator.
- Allow 30 minutes for drying between coats of **LIQUI-GEM DIAMOND**.
- For floors subject to frequent burnishing operations, apply 4 to 6 coats of **LIQUI-GEM DIAMOND**.

**MAINTENANCE DIRECTIONS:**

- Daily damp mopping removes dirt that may scratch or abrade finish. Utilize **LIQUI-GEM WASH** for all your damp mopping needs.
- After damp mopping, **LIQUI-GEM DIAMOND** can be repaired and maintained using conventional spray buffing techniques. Lightly mist a solution of **LIQUI-GEM REVITALIZE** and buff the finish to an incredible gloss.
- Or, after damp mopping, several passes with burnishing equipment will restore the gloss of floors subjected to heavy pedestrian traffic.

KEEP FROM FREEZING.



Please Recycle.

1706.051215