

LITHI-LUBE 2

High Performance Red Lithium Complex Grease

- Extreme Pressure/Anti-Wear Properties
- Outstanding Shear Stability
- Extreme Oxidations and Thermal Ability
- Enhanced Rust & Corrosion Inhibition
- Operating Range of 0° F to 350° F

NLGI #2 GC-LB CERTIFIED

1841011725



LITHI-LUBE 2 is a versatile multi-purpose lithium complex bearing grease fortified with a polymer and high-performance additives. It contains anti-wear technology designed for heavily loaded plain and multi-use anti-friction bearings operating under normal to adverse conditions. The lithium complex thickener provides a tacky, shear stable long life. It is formulated with high quality base fluids that have outstanding thermal and oxidative stability characteristics that perform exceptionally in severe applications that require higher performance.

SPECIAL FEATURES:

- NLGI GC-LB Certified
- Low Oil Bleed
- Excellent Water Resistance
- Top Tier Extreme Pressure/Anti-Wear Properties
- Outstanding Shear Stability
- Hydrodynamic Lubrication Properties
- Extreme Oxidation and Thermal Stability
- Enhanced Rust & Corrosion Inhibition
- Good Low Temperature Pumpability

APPLICATIONS:

LITHI-LUBE 2 is engineered specifically for any application requiring an excellent all-around lithium complex grease. It is a truly multi-purpose grease used in automotive, agricultural, farming, mining, cement, construction, logging, steel, and marine industries. It is highly recommended for wheel bearings of passenger cars, high performance vehicles, trucks, sport utility vehicles, motorcycles, and all other vehicles.

PREVENTION:

Eyes: Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or irritation persists, transport to nearest medical facility for additional treatment.

Skin: Flush skin with water, wash with soap and water. If irritation occurs, get medical attention. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport them to the nearest medical facility for additional treatment.

Ingestion: Do NOT induce vomiting and obtain medical attention. Have the victim rinse mouth out with water. If vomiting occurs spontaneously, keep their head below hips to prevent aspiration.

Inhalation: Move the victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

FIRE FIGHTING MEASURES:

Flammable Properties:

Base Oil Flash point: 218°C (ASTM D92) Flammable limits in air: N/A

INGREDIENTS:

Solvent Refined Heavy Paraffinic (64742-65-0)

NLGI GRADE 2

HMIS Ratings:

Health - 1, Flammability - 1 Reactivity - 0 Personal - A

CAUTION

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 14.5 OZ. (411 g)