

# AQUA LUBE

## Water Resistant Grease

**Form:** Semi-Solid

**Color:** Green or blue

**Odor:** Slight Petroleum

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**Flash Point (°F):** 455

**Specific Gravity:** 0.96 g/cm<sup>3</sup>

**Density:** 8.01 lbs/gal

**Storage Stability (at 70°F):** 1 year

### Great for use in...

- Paper Machine Wet Ends
- Winter DOT Equipment
- Steel Foundries
- Marine Equipment
- Oil Fields
- Elevators
- Boiler Operations
- Mining Equipment
- Sewage Plants
- Farm Equipment
- Air Conditioners
- Wheel Bearings

### TYPICAL SPECIFICATIONS

NLGI Grade .....	2
Color .....	Green or Blue
Thickener Type .....	Calcium Sulfonate Complex
Viscosity @ 40°C, cSt .....	220
Viscosity Index .....	97
Penetration Worked .....	265-295
Dropping Point (°F).....	+550
Timken OK Load (lbs) .....	65
Weld Load, kg, ASTM D 2596 .....	620
Load Wear Index.....	65
Wheel Bearing Leakage .....	5.0 MAX
Water Washout @ 175°F, % wt.....	3.0

HMIS®		NFPA			
Health .....	1	Severe	4	Extreme	
Flammability.....	1	Serious	3	High	Health..... 1
Physical Hazard .....	0	Moderate	2	Moderate	Flammability ..... 1
Personal Protection.....	X	Slight	1	Slight	Reactivity ..... 0
		Minimal	0	Insignificant	Special Precautions .....None