



TRIDENT

WATER TREATMENT

ULTRA PROTECT

CLEANER AND DESCALER

DANGER

Causes severe skin burns and eye damage.
Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

TRIDENT

WATER TREATMENT

ULTRA PROTECT



P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com



DANGER:

Causes severe skin burns and eye damage.
Causes serious eye damage.

PREVENTION:

Do not breathe the mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention. Immediately call a doctor, a POISON CENTER.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

CONTAINS/CAS#:

Water (7732-18-5); Potassium Hydroxide (1310-58-3); Proprietary corrosion inhibitor (Withheld); Amino-Methylene Phosphonic Acid(Not Available); Benzotriazole (95-14-7).



Please Recycle.



ULTRA PROTECT

TRIDENT ULTRA PROTECT is a water tower treatment used to inhibit scale formation, control rust and corrosion. This formulation improves water circulation and heat exchange, keeping cooling towers operating at peak performance, leading to more efficient cooling, lowering fuel and maintenance costs. Using Share's **TRIDENT ULTRA PROTECT** improves water circulation and reduces tube pressure, reducing overall fuel costs, minimizing maintenance and increasing the system's operating life.

DIRECTIONS:

Preparation: Flush cooling tower thoroughly to remove loose scale and sludge. Clean the sump, slats and intake strainers to remove algae, scale and debris. If excessive amounts of dead algae, scale and debris are present, drain tower and clean slats and sump thoroughly.

Application: Add 1 gallon of **TRIDENT ULTRA PROTECT** for every 100 gallons of cooling tower water.

Maintenance: Periodically add more **TRIDENT ULTRA PROTECT** to replace product lost through bleed-off, carryover and wind loss.

WARNING: This product can expose you to Formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS:

Health: 2; Flammability: 1; Reactivity: 0

1942.111921