

TRIDENT TOWERGUARD POLYCLEAN

Cooling Tower Water Treatment

Form: Liquid

Color: Colorless

Odor: Slight

pH: 6.0 – 7.0

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by weight): <0.5 %

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.00 g/cm³

Density: 8.35 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Water.....7732-18-5
 Acrylamide Copolymer..... Proprietary
 Potassium Hydroxide 1310-58-3

- | For Use In... |
|--------------------------|
| • Cooling Towers |
| • Evaporative Condensers |
| • Absorption Systems |
| • Chillers |
| • Humidifiers |

DIRECTIONS:

TRIDENT TOWERGUARD POLYCLEAN is for use in cooling towers 200 tons or greater. TRIDENT TOWERGUARD POLYCLEAN can be added to sump, tower basin or directly in circulation line.

Initial Application: Add 1 gallon of TRIDENT TOWERGUARD POLYCLEAN for every 3000 gallons of cooling tower water.

Daily Application: The feed rate for TRIDENT TOWERGUARD POLYCLEAN is 1 gallon for every 1000 gallons of cooling tower water.

Rapid Cleaning Application: Add 2 gallons of TRIDENT TOWERGUARD POLYCLEAN for every 3000 gallons of cooling tower water until bleed-off occurs.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None