



RUBBER in a CAN

Protective Flexible Rubber Coating

- QUICK & EASY TO USE.
- SEALS OUT MOISTURE.
- STAYS COMPLETELY FLEXIBLE.
- RESISTS SUMMER HEAT & WINTER COLD.
- WON'T CRACK OR PEEL.
- PROTECTS FROM CORROSION.

FOR INDUSTRIAL/PROFESSIONAL USE ONLY.
NOT FOR RETAIL SALE.

See back panel for additional precautions.

NET WEIGHT: 16 OZ. (454 g)

RUBBER IN A CAN provides superior protection for fender replacements, section repairs and weld joints. It also depresses sound, retards salt corrosion, and seals water leaks. RUBBER IN A CAN may be used on concrete and asphalt driveways, gutters and flashings and roofs.



DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

PREVENTION:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL:

Dispose of contents/container in accordance with local/regional/national/international regulations.

INGREDIENTS/CAS

Acetone (67-64-1); Propane (74-98-6); Toluene (108-88-3); Calcium Carbonate (1317-65-3); Xylene (1330-20-7); Carbon Black (1333-86-4); Crystalline Silica (14808-60-7).

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.

DIRECTIONS

SHAKE WELL BEFORE USING. Make sure surface is clean, dry and free of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up to the desired thickness. Remove overspray with a cloth dampened with kerosene. Coverage: 10 to 20 square feet per can. Temperature: Both surface and at use temperature should be between -10°F to 150°F.

WARNING



This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

8002.020917

Sold by:

