



Chain & Cable Lube

Chain & Cable Lube



CHAIN & CABLE LUBE is a foaming, high-speed chain and cable penetrating lubricant fortified with molybdenum additives providing maximum protection to wire ropes, cables and chains.



DANGER:

Extremely flammable aerosol. May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not breathe gas. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:

IF ON SKIN: Wash with plenty of water. **If exposed or concerned:** Get medical advice/attention. **If skin irritation or rash occurs:** Get medical advice/attention. Wash contaminated clothing before reuse.

STORAGE:

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

FOAMING LUBRICANT WITH MOLY

- PENETRATES INTO CABLES & CHAINS
- PROTECTS AGAINST FRICTION & WEAR
- WILL NOT ATTRACT DUST & DIRT
- RESISTS RUST AND CORROSION

VOC COMPLIANT

DANGER:

EXTREMELY FLAMMABLE AEROSOL. MAY CAUSE AN ALLERGIC SKIN REACTION. SUSPECTED OF CAUSING CANCER. CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

KEEP OUT OF REACH OF CHILDREN

See back panel for further cautions and first aid instructions.

NET WEIGHT: 15 ounces (425 grams)

INGREDIENTS/CAS#:

Heavy Paraffinic Petroleum Distillates (64741-88-4); Propane (74-98-6); Mineral Spirits (8052-41-3); Cocoyl Diethanolamide (68603-42-9); Solvent Naphtha (Petroleum), Medium Aliphatic (64742-88-7); Diethanolamine (111-42-2)

NFPA® RATINGS:

Health: *2; Flammability: 4; Reactivity: 0

DIRECTIONS:

SHAKE WELL BEFORE USING. Shake until ball rattles for at least 30 seconds before applying. For best application, **CHAIN & CABLE LUBE** should be used at room temperature or at temperatures above 70°F. Parts to be treated should be reasonably clean and dry. Hold can 12 to 14 inches from surface to be treated and spray to coat surface. Product will penetrate into tight spaces. Product will spray at any angle, even inverted.



WARNING: This product can expose you to diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



Please Recycle

Sold by:

8140.0129

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com