



Liqui-Gem
**Marquise
Cut Gel**
BASEBOARD STRIPPER SPRAY

**REMOVES WAX & FLOOR FINISH
FROM BASEBOARDS, STAIRS,
FLOOR EDGES, CORNERS
TILES AND PORCELAIN**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.

WARNING:

Flammable Aerosol Contains gas under pressure;
May explode if heated. Causes skin and eye irritation.

NET WEIGHT: 20 oz. (567 g)

FOR INDUSTRIAL/PROFESSIONAL USE ONLY.
NOT FOR RETAIL SALE.

LIQUI-GEM MARQUISE CUT GEL heavy duty cleaner removes copolymer floor finishes and wax from baseboards, floor edges and moldings, stairs, corners, tiles and porcelain. The special spray valve operates in the inverted position for easy application. **LIQUI-GEM MARQUISE CUT GEL's** clinging gel holds to vertical surfaces to loosen heavy accumulations of floor finish.



WARNING:

Flammable Aerosol Contains gas under pressure; May explode if heated. Causes skin and eye irritation.

PREVENTION:

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves.

RESPONSE:

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

STORAGE:

Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

DISPOSAL:

Dispose of in accordance with federal, state, and local regulations.

INGREDIENTS/CAS#: Water (7732-18-5), Butoxyethanol (111-76-2), Propane (7498-6), Butane (106-97-8), Nonoxynol (127087-87-0).

NFPA® RATING:

Health: 2; Flammability: 1; Reactivity: 0

DIRECTIONS:

- Always test this product in an inconspicuous area to be cleaned before using. Immediately wipe any overspray from furniture, walls and other surfaces.
- Shake well and hold can in inverted position.
- Hold can 6 to 10 inches from surface and spray a thin coating over areas to be stripped.
- Let stand for 3-5 minutes.
- For stubborn build-up of wax or floor finish, rub with sponge or scrub pad.
- Wipe residue from surface with wet sponge.



Please Recycle.

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.

8177.032322

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com