



CARBURETOR Cleaner

CHOKE & CARBURETOR CLEANER

- CARBURETOR LINKAGE
- AUTOMATIC CHOKEs
- BAFFLE PLATES
- MANIFOLD HEAT CONTROLS

**FOR INDUSTRIAL/PROFESSIONAL USE ONLY.
NOT FOR RETAIL SALE.**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.



This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

NET WEIGHT: 14.75 ounces (419 g.)

CARBURETOR CLEANER acts instantly on gum and varnish deposits, dissolving them to the bare metal in seconds. It also serves as an excellent penetrant to free hard-to-reach passages and sliding surfaces that are clogged or bound by gum, carbon or corrosive deposits.



DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

RESPONSE:

If exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

STORAGE:

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

DISPOSAL:

Dispose of contents/container to an approved waste disposal plant.

INGREDIENTS/CAS#: Acetone (67-64-1), Methyl acetate (79-20-9), Xylene (1330-20-7), Carbon dioxide (124-38-9), Ethyl benzene (100-41-4)

DIRECTIONS FOR USE:

Shake well before using. Stop engine. Remove air cleaner. Spray small amount into throat and outside of carburetor. Let soak 3-5 minutes, then start, run engine for several minutes for remaining deposit burn off. Repeated applications may be necessary if mechanism is extremely dirty. Automatic chokes may be easily cleaned by removing choke face plate & spraying the mechanism.

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.



Please Recycle.

8310.060115