

Slyde N' Glyde

Dry Silicone Spray

Form: Solvent-Based Aerosol

Color: Clear

Odor: Mild Solvent

pH: N/A

Solubility (in water): 40%

Flash Point (ASTM D-7821): <5°

Specific Gravity: Density: 0.76

Storage Stability (at 70°F): 1 year

This Product Contains:	CAS#
Acetone	67-64-1
Propane/n-Butane	68476-86-8
Heptane	142-82-5
Polydimethylsiloxane	63148-62-9

Great For Use In...

- Apparel & Accessory manufacturing
- Manufacturing
- Tank Closure Seals
- Plastic Products
- RV Dealers
- Hotels/motels
- Machine Shops

Directions for Use: Read cautions and directions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS				NFPA	
		Severe	4	Extreme	
Health.....	1	Serious	3	High	Health.....
Flammability.....	0	Moderate	2	Moderate	Flammability.....
Reactivity.....	0	Slight	1	Slight	Reactivity.....
Personal Protection.....	None	Minimal	0	Insignificant	Special Precautions.....
					None