

Part #:





**PART** 

**MEDIUM GRAY** 

**FAST SET EPOXY COATING** 

Mix Ratio: 2A TO 1B BY VOLUME **Cure: 2-4 HOURS** 

Net Wt.: 8.00 LBS. (3.63 KGS.)

[H315, H317, H319, H411 / P261, P264, P273, P280, P302+P352, P305+P351+P338, P333+P313, P337+P313, P362+P364, P391, P501]

## Warning

EN: Causes skin irritation. May cause an allergic skin reaction. Causes series eye irritation. Toxic to aquatic life with long lasting effects. Avoid breathing mist/vapors/spray. Wash hands thoroughly after handling. Avoid release to the environment. Wear protective gloves, clothing and eye/face protection. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Dispose of contents and containers in accordance with local, regional and international regulations.



Contains: Bisphenol A Epoxy Resin (CAS# 25058-99-8), Alkyl C12- C14 Glycidyl Ether (CAS# 68609-97-2).

12345

Batch: 1234567

KEEP OUT OF REACH OF CHILDREN.